



PIT TYPE
FECD-P CPR-M ANALOG CELL
CONCRETE DECK

OVER 95 YEARS OF COMBINED EXPERIENCE MANUFACTURING INDUSTRIAL WEIGHING EQUIPMENT

BYEK FEATURES AND SPECIFICATIONS

CERTIFICATE OF CONFORMANCE: 97-116

TYPE: Pit

SCALE CAPACITY: Up to 270,000 lbs.

CONCENTRATED LOAD CAPACITY: 80,000 lbs.

SCALE HEIGHT: 56,000 / 67,000 / 77,000 lbs.

AVAILABLE WIDTHS: 35-3/4"

WEIGHBRIDGE DECK: 6" concrete deck-deck coping supplied for field installation OPTION: Factory supplied deck sheeting and rebar (Truck Scale Accessories)

STEEL PREPARATION: Commercial blast cleaning SSPC-SP6

PAINT SYSTEM: Cross-Linked two-part Epoxy 2 to 4 mil primer base coat. Two-part UV resistant Polyurethane 2 to 4 mil top coat

LOAD CELL: 75K CPR-M analog compression column load cell, 700 Ohm, 2 mV/V Stainless steel environmentally sealed (IP68) construction

JUNCTION BOX: NEMA 4X FRP enclosure(s) and B-TEK 4-cell summing board with GDT surge protection CPR-M analog load cells utilize ground straps and base plate isolation disc

SURGE PROTECTION: Surge protection enhanced by Transfector DPS-8T AC line transient protection device

WARRANTY: 5-Year weighbridge warranty covering defects in materials and workmanship. 5-Year components warranty covering defects in materials and workmanship. 5-Year surge / lightning warranty covering CPR-M load cells and summing boards

INDICATOR: Not included with analog cell version







WWW.B-TEK.COM

1510 METRIC AVE. SW CANTON, OHIO 44706

PHONE NUMBER: 330.471.8900 TOLL FREE NUMBER: 800.266.8900 FAX NUMBER: 330.471.8909









Want more information?
Simply Point and shoot your camera phone at this code to connect directly to our website.
Need a code reader?
Visit http://www.b-tek.com/codereaders.aspx